

## SPECIFICATION SHEET FOR H<sub>2</sub>S SENSOR TYPE H2S/M-200-2E

### PERFORMANCE CHARACTERISTICS


Nominal Range	0 – 200 ppm
Maximum Overload	Nd
Expected Operation Life	2 years in air
Output Signal	250 ± 50 nA/ppm
Resolution	0.2 ppm
Temperature Range	- 40 °C to + 50 °C
Pressure Range	Atmospheric ± 10 %
Pressure Coefficient	No data
t <sub>90</sub> Response Time	< 60 sec
Relative Humidity Range	15 % to 90 % R.H. non-condensing
Typical Baseline Range (pure air, 20°C)	- 1 ppm to + 1 ppm
Maximum Zero Shift (+20°C to +40 °C)	0.2 ppm equivalent
Expected Long Term Output Drift	< 2 % signal loss/month
Recommended Load Resistor	10 Ohm
Bias Voltage	Not required
Repeatability	< 2 % of signal
Output Linearity	Linear

### PHYSICAL CHARACTERISTICS


Weight	~ 5.4 g
Position Sensitivity	None
Storage Life	Six months in container
Recommended Storage Temperature	5 °C – 20 °C
Warranty Period	12 months from date of dispatch

### Miniature-Size Outline Dimensions

BOTTOM VIEW



SIDE VIEW



### CROSS-SENSITIVITY DATA

Interfering Gas	Concentration	Reading
CO	300 ppm	< 3 ppm
H <sub>2</sub>	300 ppm	< 3 ppm

Performance data conditions:  
20 °C, 50% RH and 1013 mbar

### APPLICATIONS

For Portable Gas Detectors

The data contained in this document is for guidance only. Membrapor AG accepts no liability for any consequential losses, injury or damage resulting from the use of this document or the information contained within it. The data is given for guidance only. Customers should test under their own conditions, to ensure that the sensors are suitable for their own requirements.

REV.: 6/2009

Page 1 of 1

Phone: +41 43 311 72 00  
Fax : +41 43 311 72 01  
Email: info@membrapor.ch  
www.membrapor.ch

MEMBRAPOR AG  
Birkenweg 2  
CH-8304 Wallisellen  
Switzerland